

RMT8Q(M)4000




그림 1




그림 2




그림 3




그림 4



절입각
88°

- 축방향 경사각 : -6°
- 반경방향 경사각 : -11°~6°

(mm)

형번	재고	CICT	DC	DCX	DHUB	DCON-MS	KWW	LF	APMX	kg	그림	
RMT8Q (RMT8QM)	4080R	●	5	80	81.1	57	25.4(27)	9.5(12.4)	50	5	1.2	1
	4080R-M		6	80	81.1	57	25.4(27)	9.5(12.4)	50	5	1.2	1
	4100R	●	6	100	101	67	31.75(32)	12.7(14.4)	50	5	1.7	2
	4100R-M	●	8	100	101	67	31.75(32)	12.7(14.4)	50	5	1.7	2
	4125R	● (●)	8	125	126	87	38.1(40)	15.9(16.4)	63	5	3.5	2
	4125R-M		10	125	126	87	38.1(40)	15.9(16.4)	63	5	3.5	2
	4160R	●	10	160	161	107	50.8(40)	19.1(16.4)	63	5	5.6	2
	4160R-M		14	160	161	107	50.8(40)	19.1(16.4)	63	5	5.6	2
	4200R		12	200	200.9	130	47.625(60)	25.4(25.7)	63	5	7.5	3
	4200R-M		18	200	200.9	130	47.625(60)	25.4(25.7)	63	5	7.5	3
	4250R		16	250	250.9	180	47.625(60)	25.4(25.7)	63	5	12.5	3
	4250R-M		22	250	250.9	180	47.625(60)	25.4(25.7)	63	5	12.5	3
	4315R		20	315	315.9	240	47.625(60)	25.4(25.7)	63	5	19.9	4
	4315R-M		28	315	315.9	240	47.625(60)	25.4(25.7)	63	5	19.9	4

()메트릭 사이즈, ●: 재고 관리 형번

적용인서트

SNC(M)F-MF SNC(M)F-MM



형번	써메트	코팅										추경			페이지				
		CN30	NC5330	NCM325	NCM335	NCM535	NCM545	PC2505	PC2010	PC3700	PC6100	PC9630	PC9540	PC5300		PC5400	A30	G10E	H01
SNCF	1206QNN-MF									●									B23
	1206QNN-MM									●									
SNMF	1206QNN-MF									●									B23
	1206QNN-MM									●									

적용아버

커터형번	범용아버	NC용 아버		
		RMT8Q	RMT8QM	
RMT8Q (RMT8QM)	□080R	NT*□□(M/U)-FMA25.4-25	BT**□□-FMA25.4-□□	FMC27
	□100R	NT*□□(M/U)-FMA31.75-□□	BT**□□-FMA31.75-□□	FMC32
	□125R	NT*□□(M/U)-FMA38.1-□□	BT**□□-FMA38.1-□□	FMB40
	□160R	NT*□□(M/U)-FMA50.8-□□	BT**□□-FMA50.8-□□	
	□200R	NT*□□(M/U)-FMA47.625-25, KCP-8***	BT**□□-FMA47.625-□□	FMB60
	□250R			
□315R	KCP-8***(센터링플러그)			

*□□-NT번호 **□□-BT번호 ***밀링5호이상

부품

부품명					
적용공구직경	스크류	스크류	스프링	레치(Latch)	렌치
Ø80~Ø315	ETKA0523	KHB0417	SPR0315	LTC05SR-RM4	TW20-100

적용인서트 B23 적용아버 및 볼트 E94 ~ E96