

RM14XCM-XN06




그림 1




그림 2



절입각
51°

- 축방향 경사각 : -6°
- 반경방향 경사각 : -9°

형 번	재고	CICT	DC	DCX	DHUB	DCON-MS	KWW	LF	APMX	kg	그림	
RM14XCM	050R-22-5-XN06	●	5	50	58.562	42	22	10.4	40	3.5	0.3	1
	050R-22-6-XN06	●	6	50	58.562	42	22	10.4	40	3.5	0.3	1
	063R-22-6-XN06	●	6	63	71.562	42	22	10.4	40	3.5	0.5	1
	063R-22-8-XN06	●	8	63	71.562	42	22	10.4	40	3.5	0.6	1
	080R-27-6-XN06	●	6	80	88.561	57	27	12.4	50	3.5	1.0	1
	080R-27-8-XN06	●	8	80	88.561	57	27	12.4	50	3.5	1.1	1
	080R-27-10-XN06	●	10	80	88.561	57	27	12.4	50	3.5	1.1	1
	100R-32-10-XN06	●	10	100	108.561	67	32	14.4	50	3.5	1.6	1
	100R-32-12-XN06	●	12	100	108.561	67	32	14.4	50	3.5	1.6	1
	125R-40-12-XN06	●	12	125	133.561	90	40	16.4	63	3.5	3.4	1
	125R-40-14-XN06	●	14	125	133.561	90	40	16.4	63	3.5	3.4	1
	160NR-40-16-XN06	●	16	160	168.561	110	40	16.4	63	3.5	4.9	2
	160NR-40-18-XN06	●	18	160	168.561	110	40	16.4	63	3.5	4.8	2

※ XNMX060608-□□ 적용 시 APMX = 4.8mm

● : 재고 관리 형번

적용인서트

형 번	써메트	코팅										초경			페이지			
		NC5330	NCM325	NCM335	NCM535	NCM545	PC2505	PC2010	PC3700	PC6100	PC9530	PC9540	PC5300	PC5400		PC5535	A30	G10E
XNMX	0606XNR-ML				●				●		●	●	●	●				
	0606XNR-MM							●	●			●	●	●				
	060608-ML										●	●	●	●				
	060608-MM								●	●			●	●				

적용아버

RM14XCM	커터형번	DCON-MS	적용아버
	050R	22	BT□□-FMC22-□□
	063R		
	080R	27	BT□□-FMC27-□□
	100R		
	125R	32	BT□□-FMC32-□□
	160R		40

부품

부품명	스crews	렌치
적용공구직경	FTKA0412B	TW15S
Ø50~Ø160		

적용인서트 B32 적용아버 및 볼트 E96